

Comment on “Dense coding in entangled states”

O. Akhavan^{1,2,*} and A.T. Rezakhani^{1,†}

¹*Department of Physics, Sharif University of Technology, P.O. Box 11365-9161, Tehran, Iran*

²*Institute for Studies in Theoretical Physics and Mathematics (IPM), P.O. Box 19395-5531, Tehran, Iran*

In a recent Brief Report, Lee *et al.* [L. Lee, D. Ahn, and S.W. Hwang, Phys. Rev. A **66**, 024304 (2002)] have claimed that using pairwise entangled qubits gives rise to an exponentially more efficient dense coding when two parties are involved than using maximally entangled qubits shared among N parties. Here, we show that their claim is not true.

PACS numbers: 03.67.Hk, 03.65.Ud

Dense coding protocol as suggested by Bennett and Wiesner [1] is to send two bits of classical information by sending just one qubit from the sender to the receiver which have a shared entanglement. So, comparing with classical world where there is no entanglement, one gets a more dense way of information transfer by using quantum channels.

Recently, Lee *et al.* [2] have considered two different multiqubit schemes for dense coding and compared their efficiency. In the pairwise scheme, Alice and Bob share N separated maximally entangled pairs, so this scheme is equivalent to N separate dense coding schemes. In their the maximally entangled scheme, Alice has N qubits and Bob possesses one, which are prepared in a $N + 1$ maximally entangled qubits. The number of different unitary operators which can be constructed in the first scheme is 4^N corresponding to the number of different messages which can be sent. Since if we have M different messages we can codify them in $\log_2 M$ bits of information, then $\log_2 4^N = 2N$ bits of information can be transferred by the pairwise scheme from Alice to Bob, by sending N particles. Their essential mistake is just here by which they have concluded that number of bits is 2^N , which is incorrect. Therefore the rates of information gain (bits per unit time) that they have deduced in their Eqs. (6) and (7) for the pairwise and maximally entangled schemes must change into

$$\begin{aligned} r_p &= \frac{2N}{N(t_h + t_c)} \\ r_m &= \frac{N + 1}{t_h + Nt_c} \end{aligned} \quad (1)$$

where t_c and t_h are operation times for CNOT and Hadamard gates, respectively. If t_c and t_h are assumed equal it is seen that, $r_p = r_m = \frac{1}{t_c}$, and there is no exponential efficiency in the pairwise scheme. Therefore considering N different Alices or combining them as a sole Alice (which changes the number the parties involved but not the number of sent particles) cannot lead into a more efficient protocol as they have claimed. This is in accordance with the result of Bose *et al.* [3]. As well, a more efficient (logarithmically) has been proposed recently in [4].

Also, it should be noted that a more reasonable measure of efficiency of the scheme can be the number of bits transferred in the protocol per needed time per sent particles. By considering this we have

$$\begin{aligned} r_p &= \frac{2}{N(t_h + t_c)} \\ r_m &= \frac{N + 1}{N(t_h + Nt_c)}. \end{aligned} \quad (2)$$

Now these quantities give more better sense of efficiency of the protocols, though, the number of the sent particles are the same here. This concept of efficiency also applies to the scheme of Bose *et al* [3].

-
- [1] C.H. Bennett and S.J. Wiesner, Phys. Rev. Lett. **69**, 2881 (1992).
 - [2] L. Lee, D. Ahn, and S.W. Hwang, Phys. Rev. A **66**, 024304 (2002).
 - [3] S. Bose, V. Vedral, and P.L. Knight, Phys. Rev. A **57**, 822 (1998).
 - [4] O. Akhavan, A.T. Rezakhani, and M. Golshani, Phys. Lett. A **313**, 261 (2003).

*Electronic address: akhavan@mehr.sharif.edu

†Electronic address: tayefehr@mehr.sharif.edu